PLC-XW60

- Brightness: 2000 ANSI Lumens

- Resolution, native: 1024 x 768 (XGA)

- PIN code security

- Direct power off

- Ultra light weight (1.6kg)

- 3 year warranty

PLC-XW60

TECHNICAL DETAILS	PLC-XW60
Category	Business & Education
Panel	3 x 0.63" TFT p-Si (4:3), Micro lens
Lamp	165 W UHP
Brightness ANSI lumens	2000
Lamp Service Life	3500 h (eco mode), 2000 h (normal mode)
Fan Noise	30.5 dBA (eco mode), 34.3 dBA (normal mode)
Standard Lens	F=1.77-1.99, f=17.4-21.1mm
Throw Distance Ratio	1.33–1.62:1
Throw Distance	1.1m – 10m
Contrast Ratio	400:1
Resolution in pixels	1,024 x 768 (XGA)
Image size min–max (diagonal)	40" – 300"
Uniformity	85%
Bandwith/Frequency	110MHz, Horizontal 15kHz~100kHz, Vertical 50Hz~100Hz
Colour Systems	NTSC/ PAL/ SECAM/ NTSC4.43/ PAL-M/ PAL-N
Connections	Input 1: D-Sub15 (RGB/Component/S-Video)
	Input 2: D-sub15 (RGB)/ Monitor out
	Input 3: RCA x 1
	Audio Input: Mini Jack x 1, RCA x2
	Control Port: Mini Din 8-pin x 1
Keystone Correction	vertical ±20°
Up/Down Ratio	6:1
HDTV Signals	1080i/ 50, 1080i/ 60, 1035i, 720p
Computer Compatibility	UXGA / WXGA / SXGA+/ SXGA / XGA / SVGA / VGA / MAC
Zoom/Focus	1.2x / Manual
Power Consumption/Voltage	188 W (eco mode), 219 W (normal mode)
Warranty	3 years
Dimensions (W x H x D)	264 x 55 x 188mm
Weight	1.6kg
Standard Accessories	Quick Reference guide, Owners manual (CD ROM), PIN code label, Lamp replacement label, Power cord, Remote control, Soft carry bag
Optional Accessories	Component(3xRCA)-Dsub15 cable (POA-CA-COMPVGA), Scart-Dsub cable (POA-CA- SCART)

* You can use the distance calculator at www.sanyo.co.uk to determine exact image sizes and distances

Technical specifications subject to change without notice. Status 09/2007

Telephone: 01923 246363

Email: info@sanyo.co.uk

Visit: www.sanyo.co.uk